



| Particulars | | | |
|---------------------------------|--------------------------------|-----------|------------|
| Nominal Capacity | | 2 t | |
| Hand Chain | Folded Hand Chain Length | 3.0 m | |
| | Length from Bottom of Beam : E | 2.8 m | |
| Min. Radius for Curve | | 1500 mm | |
| Flange Width | : B | 82~153 mm | 154~305 mm |
| Max. Dimension of Trolley Width | : G | 385 mm | 535 mm |
| Mass | | 19 kg | 20 kg |

Note:
 For Manual Chain Hoist
 The trolley can be installed on either tapered or flat flange.

| | | | | | | | | | | |
|------|-----|----------|--|--|------|--------------|--------------|--------------|--------------|-------------------------------|
| | | | | | | APPROVED | CHECKED | DESIGNED | DRAWN | TITLE |
| | | | | | | T. Hiroshima | T. Ogata | M. Ono | M. Ono | 2t TS SERIES GEARED TROLLEY |
| | | | | | | 2024. 04. 26 | 2024. 04. 26 | 2024. 04. 26 | 2024. 04. 26 | CODE TSG020 SCALE 1:3 |
| REV. | QTY | CONTENTS | | | DATE | DRAWN | APPROVED | KITO | | DWG. NO. T7GF020-12100 REV. 0 |