



| Particulars                     |                                |           |            |
|---------------------------------|--------------------------------|-----------|------------|
| Nominal Capacity                |                                | 3 t       |            |
| Hand Chain                      | Folded Hand Chain Length       | 3.0 m     |            |
|                                 | Length from Bottom of Beam : E | 2.8 m     |            |
| Min. Radius for Curve           |                                | 1700 mm   |            |
| Flange Width                    | : B                            | 82~153 mm | 154~305 mm |
| Max. Dimension of Trolley Width | : G                            | 398 mm    | 548 mm     |
| Mass                            |                                | 27 kg     | 29 kg      |

Note:  
 For Electric Chain Hoist  
 The trolley can be installed on either tapered or flat flange.  
 82 to 89mm available for only straight beam.

|      |     |          |  |  |              |              |              |                        |                             |
|------|-----|----------|--|--|--------------|--------------|--------------|------------------------|-----------------------------|
|      |     |          |  |  | APPROVED     | CHECKED      | DESIGNED     | DRAWN                  | TITLE                       |
|      |     |          |  |  | T. Hiroshima | T. Ogata     | M. Ono       | M. Ono                 | 3t TS SERIES GEARED TROLLEY |
|      |     |          |  |  | 2024. 04. 26 | 2024. 04. 26 | 2024. 04. 26 | 2024. 04. 26           | CODE TSG030 SCALE 1:3       |
| REV. | QTY | CONTENTS |  |  | DATE         | DRAWN        | APPROVED     |                        |                             |
|      |     |          |  |  |              |              |              | DWG. NO. T7GE030-12100 | REV. 0                      |